PRODUCT CHARACTERISTIC SHEET

PLEASE READ BEFORE USING!

Material: CONVEX® GearWrap™ Clear and White 8 mil.

General Description: Clear and White, soft, flexible vinyl with a clear permanent acrylic adhesive. Different combinations of Convex® or Pro-Shield™ laminates may be used to achieve a variety of decal thicknesses.

Thickness:	8 mil. vinyl with 1.2 mil of adhesive
Outdoor Life:	2 years
Shelf Life:	1 year stored at 70 F & 50%RH
Service Temperature Range:	(-40° F to 176° F)
Minimum Application Temp.:	50° F

Adhesive Properties:

General purpose adhesive works on most surfaces. Gearwrap™ adhesive is formulated to remove cleanly from most surfaces for up to a year after it is applied.

Tests performed | results:

Ulitmate Peel from	Average OZ/IN	Test Method	
Acrylic	70	ASTM D 903 (Modified for 72 hour dwell time)	
Painted Polycarbonate	27		
Polypropylene	14		
Glass	56		
Stainless Steel	54		
Expected Shear	5	ASTM D 3654 Method A	a. 1 hrl dwell
-	5	ASTIVID 3034 Metriod A	
Room Temp (hours)			b. 1 sq. in. surface
			c. 4 lb. load
Tack (gm/sq cm)	330	ASTM D 2979	

Recommended Application Techniques:

On curved surfaces such as helmets, apply by rubbing from the center out. When using Convex as a Laminate, as it is separated from the liner, if there is too much drag tension applied to the supply roll, it can stretch and curl up immediately after it is cut on a plotter. Laminate with a cold pressure sensitive laminator or by hand.

GSP Software Settings:

In Gerber's Plot program, click on the "123" button then on the substitute button and select vinyl. Select 3M 220 Premium or Gerber ImageCal from the pull-down menu as the vinyl to print on. If you are using laminates on top of the base material, you will have to determine the best cutter settings by test cutting the finished construction.

USE A 45° blade or 60° BLADE on any combination of material 8 mil or thicker.

Disclaimer

All of the descriptive information listed above is our recommendation only. This information does not suggest or constitute a written or verbal warranty or guaranty of any kind by the manufacturer or distributor of this product. Although this material can be printed on with some solvent based printers, the surface characteristics of the material can change from roll to roll, and failure of optimal printing results are not a basis for returning the product. Purchasers of this product shall be responsible for independently determining the suitability of the material for the intended application. GT0121 Gerber Technology



Material Safety Data Sheet (MSDS)

CONVEX® GearWrap™ Clear & White 8 mil. **Material Name:**

Gerber Technology

Date Prepared:

Company:

Address: 24 Industrial Park Rd. W

and RoHS2, EU Directive 2011/65/EU

General Description: Clear soft flexible vinyl with a clear permanent acrylic adhesive.

Tolland, CT 06084-2806

Phone:

800-222-7446

RoHS, EU Directives 2002/95/EC and 2003/11/EC

Composition and information on ingredients:

Individual components of this product do not contribute to any known hazards.

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200): NONE

UL Recognized: NO **ROHS Compliant*:** YES

YES

REACH Compliant:

Hazards Identification:

None

No significant toxic hazard. When burned may produce toxic fumes.

CHRONIC: No significant toxic hazard.

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA, or ACGIH as a carcinogen.

First Aid Measures:

ACUTE:

Emergency and First Aid Procedures:

POTENTIAL HEALTH EFFECTS:

ROUTES OF ENTRY:

Inhalation: N/A Skin: N/A Eves: N/A Inaestion: N/A

Accidental Release Measures: N/A

Handling and Storage:

No special handling required other than storing away from

excessive heat sources.

Fire Fighting Measures:

Flash Point: N/A Method Used: N/A **Auto-ignition Temperature** N/A

Flamable limits in Air % by Volume: LEL: N/A. UEL: N/A

Extinguishing Media: Multi-rated ABC extinguisher or water

Unusual Fire and Explosion Hazards: None

Special Fire Fighting Procedures: In case of fire, use self-contained breathing

apparatus and full protective equipment - all fires liberate toxic gases.

Exposure Controls and Personal Protection:

Respiratory Protection: None required

Skin Protection: No precautions required

Eye Protection: None required Exposure Guidelines: None established **Engineering Controls:** None required

Toxicological Information:

Carcinogen Status: NTP: NONE IARC: NONE OSHA: NONE

Ecological Information: No Data Avaialble **Transport Information:**

> TRANSPORTATION AND HAZARDOUS MATERIALS DESCRIPTION: Not a hazardous material for DOT shipping.

Disposal Considerations: Waste Disposal:

Dispose of in accordance with Local, State and Federal regulations.

Other Information:

The information contained herein is based on the data available to the OEM, and is believed to be correct. However, Gerber Technology makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. Gerber Technology and it's distributors assume no responsibility for injury from the use of the product described herein.

Physical and Chemical properties:

Vapor Pressure (mm Hg)	N/A	Boiling Point:	N/A
Vapor Density (air = 1):	N/A	Melting Point:	N/A
Appearance and odor:	N/A	Reactivity of water:	N/A
Specific Gravity (H 0=1)	N/A	Solubility in water:	N/A

Stability and Reactivity:

N/A Stability:

Fire or Excessive Heat Conditions to avoid:

Incompatibility: None Hazardous Decomposition Products: None

Hazardous Polymerization: Will not occur.

Regulatory Information:

OSHA STANDARD CFR 29, PART 1910.1200: This product is considered to be an "article" under this standard.

SARA 313 INFORMATION: This product contains no substances at or above the reporting threshold subject to the reporting requirement of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 371, based on available data.

CALIFORNIA PROPOSITION 65: The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986. Warning this product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. This product contains up to 0.01% Toluene in the adhesive.