



## Gerber CarpetApp 2595R9C

**ImagePerfect™ 2595R9C CarpetApp is a white textured vinyl with a non-slip surface and a semi-permanent adhesive that is engineered for use in short-term, indoor floor graphic installations on low-pile carpets. It has been specially created for digital printing on large-format inkjet printers and is suitable for printing with eco solvent and solvent inks as well as UV-cured and latex inks.**

ImagePerfect™ 2595R9C CarpetApp has been specifically engineered for use as a short-term, printable floor graphic product on low-pile carpets (and carpet tiles). It can be used for installations such as promotional advertising, point-of-sale and point-of-purchase promotions, temporary wayfinding graphics and public information displays. As such, it will be used in retail locations, offices, meeting rooms, hotels, trade shows, exhibitions, airports, museums, cinemas, casinos, etc. It can also be used on the flat areas of most textile seats in locations such as the waiting areas at airports and hospitals, as well as textile seats in public transport such as busses and trains. IP CarpetApp delivers high levels of print quality with a large color gamut that ensures colorful images with vibrant area in-fills. The adhesive system delivers perfect adhesion on low-pile carpets and should allow for quick and clean removability, leaving no adhesive residue on the substrate after removal of the product. The product does not require the use of an additional laminate, delivering inherent scuff-resistance and a non-slip surface (R9).

Attention: It is strongly recommended for the product to lay flat during the drying process. In order to avoid potential lifting of the product, we would recommend that corners are rounded rather than cut to a sharp 90° angle. Surface preparation: In order to achieve process-secure application, it is essential that the substrate is totally dry and completely free of dust, dirt and debris before the product is installed. As such, we would recommend that the substrate is brushed and vacuumed before the IP CarpetApp is applied and, if the substrate is wet, we would recommend that it should be dried via portable heating, again before the product is installed. For application, the substrate should have a surface temperature of no less than 59°F

### SPECIFICATIONS

Property	Description
Film	Textured non-slip vinyl
Film Color	White, Matte
Thickness	8 mil
Adhesive	Solvent based, semi-permanent
Liner	PE-coated silicone paper
ANTI SLIP rating	R9 (DIN 51130:2014)
Temperature range	-22°F to +194°F (-30°C to +90°C)
Durability	3 months (depending on the application)
Flame Retardancy	B-s1, d0
Shelf life	12 months, 68°F (20°C) / 50% humidity

Technical specifications are subject to change without prior notice. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed or other variables. The specifications and information on physical and chemical characteristics is based upon testing believed to be reliable. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for its specific use.

## CONTACT INFORMATION

For help with questions concerning Gerber products, please call your distributor or Gerber Customer Service at 1-800-222-7446 or (860)871-8082. Visit us on the Internet at [www.gerbertechnology.com/signage](http://www.gerbertechnology.com/signage) to learn more about our many other foils, materials and equipment.

When sold by Gerber, use only the corresponding Gerber Product Bulletin to determine product details, including but not limited to appropriate uses, warranty and processing.

Gerber Scientific Products is a Registered Trademark of Gerber Technology.

ImagePerfect is a Trademark of Spandex.

**©2020 Gerber Technology. All Right Reserved**

<b>Category:</b> LARGE FORMAT	<b>FastFact #:</b> NA	<b>Supplied by:</b> Aftermarkets	<b>Last Modified:</b> 10/30/20
-------------------------------	-----------------------	----------------------------------	--------------------------------